

AD-A105 270

AERONAUTICAL RESEARCH LABS MELBOURNE (AUSTRALIA)
FLIGHT TRIAL OF THE AIRCRAFT FATIGUE DATA ANALYSIS SYSTEM (AFDA--ETC(U))
DEC 80 P J HOWARD
ARL/STRUC/NOTE-466

F/G 1/3

NL

UNCLASSIFIED

1 - 1
AC
A105270

END
DATE
FILMED
10 81
DTIC



DEPARTMENT OF DEFENCE

DEFENCE SCIENCE AND TECHNOLOGY ORGANISATION

AERONAUTICAL RESEARCH LABORATORIES

MELBOURNE, VICTORIA

STRUCTURES NOTE 466 ✓

**FLIGHT TRIAL OF THE AIRCRAFT FATIGUE DATA
ANALYSIS SYSTEM (AFDAS) MK 2 PROTOTYPE**

by

P. J. HOWARD

DTIC
S **OCT 8 1981**
A

DTIC FILE COPY

Approved for Public Release.



© COMMONWEALTH OF AUSTRALIA 1981

COPY No 22

DECEMBER 1980

81 10 8 006

AD A105270

DEPARTMENT OF DEFENCE
DEFENCE SCIENCE AND TECHNOLOGY ORGANISATION
AERONAUTICAL RESEARCH LABORATORIES

STRUCTURE NOTE-466

**FLIGHT TRIAL OF THE AIRCRAFT FATIGUE DATA
ANALYSIS SYSTEM (AFDAS) MK 2 PROTOTYPE**

by

P. J. HOWARD

SUMMARY

A prototype version of the Aircraft Fatigue Data Analysis System (AFDAS) has been evaluated in flight trials by a comparison with continuously recorded data. Over a limited period of test the range-mean-pairs count of strain cycles was the same for both sets of data, and the gains calculated for the AFDAS are identical to those deduced from the continuous record.

POSTAL ADDRESS: Chief Superintendent, Aeronautical Research Laboratories,
Box 4331, P.O., Melbourne, Victoria, 3001, Australia.

DOCUMENT CONTROL DATA SHEET

Security classification of this page: Unclassified

-
- | | |
|---|--|
| 1. Document Numbers
(a) AR Number:
AR-002-249
(b) Document Series and Number:
Structures Note 466
(c) Report Number:
ARL-Struc-Note-466 | 2. Security Classification
(a) Complete document:
Unclassified
(b) Title in isolation:
Unclassified
(c) Summary in isolation:
Unclassified |
|---|--|
-

3. Title: FLIGHT TRIAL OF THE AIRCRAFT FATIGUE DATA SYSTEM
(AFDAS)—MK 2 PROTOTYPE

- | | |
|---|-------------------------------------|
| 4. Personal Author(s):
Howard, P. J. | 5. Document Date:
December, 1980 |
|---|-------------------------------------|
-
6. Type of Report and Period Covered:
-

- | | |
|---|---|
| 7. Corporate Author(s):
Aeronautical Research Laboratories | 8. Reference Numbers
(a) Task:
AIR 78/052
(b) Sponsoring Agency:
DEFAIR |
|---|---|
-

- | | |
|--------------------------|--|
| 9. Cost Code:
24 1045 | 11. Computer Program(s)
(Title(s) and language(s)): |
|--------------------------|--|
-

10. Imprint (publishing establishment):
Aeronautical Research Laboratories,
Melbourne

12. Release Limitations (of the document): Approved for public release

12.0. Overseas:	N.O.	P.R.	1	A	B	C	D	E
-----------------	------	------	---	---	---	---	---	---

13. Announcement Limitations (of the information on this page): No limitations

- | | | |
|--|--|-----------------------------------|
| 14. Descriptors:
Flight tests
Fatigue life
Stress cycle
Monitors | Data recorders
Measuring instruments
Data storage devices
AFDAS | 15. Cosati Codes:
1403
0102 |
|--|--|-----------------------------------|
-

16. **ABSTRACT**

A prototype version of the Aircraft Fatigue Data Analysis System (AFDAS) has been evaluated in flight trials by comparison with continuously recorded data. Over a limited period of test the range-mean-pairs count of strain cycles was the same for both sets of data, and the gains calculated for the AFDAS are identical to those deduced from the continuous record.

CONTENTS

	Page No.
1. INTRODUCTION	1
2. DESCRIPTION OF SYSTEMS	1
2.1 AFDAS	1
2.2 AFTRAS	2
2.3 Gauge Installation	3
2.4 Calibration	3
3. TRIALS AND ANALYSIS	3
3.1 Flight Profiles	3
3.2 Data Analysis—Range-Mean-Pair Count	4
3.3 Data Analysis—Estimate of Gain	4
3.4 Data Analysis—Comparison of Memory Channels	5
4. CONCLUSIONS	5
REFERENCES	
TABLES	
FIGURES	
DISTRIBUTION	

1. Classification For
 2. Classification
 3. Classification/
 4. Classification Codes
 5. Classification
 6. Classification
 7. Classification
 8. Classification
 9. Classification
 10. Classification
 11. Classification
 12. Classification
 13. Classification
 14. Classification
 15. Classification
 16. Classification
 17. Classification
 18. Classification
 19. Classification
 20. Classification
 21. Classification
 22. Classification
 23. Classification
 24. Classification
 25. Classification
 26. Classification
 27. Classification
 28. Classification
 29. Classification
 30. Classification
 31. Classification
 32. Classification
 33. Classification
 34. Classification
 35. Classification
 36. Classification
 37. Classification
 38. Classification
 39. Classification
 40. Classification
 41. Classification
 42. Classification
 43. Classification
 44. Classification
 45. Classification
 46. Classification
 47. Classification
 48. Classification
 49. Classification
 50. Classification
 51. Classification
 52. Classification
 53. Classification
 54. Classification
 55. Classification
 56. Classification
 57. Classification
 58. Classification
 59. Classification
 60. Classification
 61. Classification
 62. Classification
 63. Classification
 64. Classification
 65. Classification
 66. Classification
 67. Classification
 68. Classification
 69. Classification
 70. Classification
 71. Classification
 72. Classification
 73. Classification
 74. Classification
 75. Classification
 76. Classification
 77. Classification
 78. Classification
 79. Classification
 80. Classification
 81. Classification
 82. Classification
 83. Classification
 84. Classification
 85. Classification
 86. Classification
 87. Classification
 88. Classification
 89. Classification
 90. Classification
 91. Classification
 92. Classification
 93. Classification
 94. Classification
 95. Classification
 96. Classification
 97. Classification
 98. Classification
 99. Classification
 100. Classification

1. INTRODUCTION

An Airborne Fatigue Data Analysis System (AFDAS) developed by British Aerospace Australia Ltd. (B.Ae.A.) from an original concept proposed by the Aeronautical Research Laboratories (ARL) has been flight tested in a Mirage III-0 aircraft (A3-002). This note compares data obtained from AFDAS with similar data obtained from continuous time histories recorded digitally on magnetic tape using an ARL recording system (AFTRAS) during trials conducted between 6 September and 9 November 1979.

2. DESCRIPTION OF SYSTEMS

2.1 AFDAS

Both AFDAS and AFTRAS have been described.^{1,2} The airborne component of AFDAS, the strain-range-pair counter (SRPC) detects turning points in strain (or other parameter); pairs peaks and troughs according to the range-mean-pairs algorithm³ and stores the information in a 14×14 half-matrix. Eight input signals can normally be accepted, but in these trials only two strain gauge amplifiers were available so that only two bridges could be interrogated. These were 21C on fin post (Fig. 1) and 18T on wing main spar (Fig. 2). The test of the instrument was broadened slightly by routing these signals to memory channels 0 and 2 (21C) and 1, 3 and 4 (18T). Channels 5-7 were unconnected and the internal offset was set offscale (Fig. 3). Signals in AFDAS are quantised at a series of levels, labelled 0-15, which are defined by bounding threshold strains. To ease discussion these thresholds are symbolised ϵ_j , so that the strain separating level 3 from level 4, for an ascending signal is ϵ_4 . For the instrument $\epsilon_3 \approx \epsilon_4$. All strain values $< \epsilon_0$ or $> \epsilon_{15}$ are stored in the appropriate outer level, so that an ill-chosen offset or gain will be characterised by many counts in one or both of these extreme levels. The SRPC was mounted in the instrumentation bay, and could be switched on or off from the cockpit. Readout was performed by a ground-based interrogator display and recording unit (IDRU) which transfers range pairs, pending (unpaired) turning points, terminal signal level and direction and documentary data to a tape cassette, which is later read into a computer.

Printouts from the computer formed one half of the primary data for the comparison. The values ϵ_j are calculated from known circuit parameters using the following relation

$$\epsilon_j = \frac{4K(\epsilon_j V_j - V_k) \times 10^6}{G \times B \times V_r \times A} \text{ microstrain } (\mu\epsilon)$$

where K = lead resistance factor, 1.0117 = assumed for all gauges,

$\epsilon_j V_j$ = counter threshold voltage,

V_k = offset voltage; = 0 for 21C = 1.54 V for 18T,

G = gauge factor = 2.09,

B = bridge factor = 2.66

μ = Poisson's ratio = 0.33,

V_r = bridge reference voltage = 5 V,

A = amplifier gain: = 379 for 21C = 263.5 for 18T.

V_k and A are fixed by selection of precision resistors, which, in the interest of stability, are hard wired into the amplifier circuit. Values of $\epsilon_j V_j$ are listed in Table 1, along with ϵ_j calculated by B.Ae.A. (column 1) and recalculated at ARL (column 2). Values in the two columns differ

because of slight differences (now resolved) in values of μ , K , and G used at the two establishments. ARL values are consistent with values used in a similar calculation for AFTRAS.

2.2 AFTRAS

This equipment is designed for versatility rather than as a long-term fixed installation. Data are generally recorded digitally in computer compatible format on $\frac{1}{2}$ " tape on 7" reels. Gain and offset are easily adjustable by potentiometer and so must be tracked by the instrumentation. This is effected by preceding each record by a sequence of calibration pulses which are obtained by bridging the active gauges by precision resistors and, for estimating offset, removing the bridge supply. The calibration (cal) signals are treated to the same processing as the data, and serve as scaling factors to transform the final output, in computer units, to engineering units of strain. Cal equivalents and other pertinent data for these trials and for an earlier calibration flight are listed in Table 2. The relation between strain and circuit values is obtained from the following expressions.⁴

The amplifier output, V_0 , is related to the strain, ϵ , by

$$\frac{V_0}{V_r} = \frac{NGB}{4K} \epsilon \cdot \frac{R_g}{R_A} \cdot \frac{1}{1 + \frac{G\epsilon}{2}(1-\mu) \left(1 + \frac{R}{2R_n + R}\right)} \quad (1)$$

and the amplifier output for a calibration step, positive to negative, V_C , is given by

$$\frac{V_C}{V_r} = \frac{R_g}{R_A} \cdot \frac{(R + 2R_L)}{(2R_C + R)} \quad (2)$$

where V_r = bridge excitation voltage,

R = gauge resistance = 350 Ω ,

R_L = lead resistance, $\sim 2.05 \Omega$,

R_L = calibration resistor value,

R_g = amplifier first stage gain resistor = 47K Ω ,

$R_A = R/2 + R_n$,

R_n = amplifier input resistance = 180 Ω ,

G = gauge factor = 2.09,

B = bridge factor = $2(1 + \mu) = 2.66$,

$K = 1 + \frac{2R_L}{R}$, lead resistance factor,

$N = 1 - \frac{R}{4R_b} \left\{ 1 + \frac{(1-\mu)}{(1+\mu) \left(1 + \frac{R}{2R_b}\right)} \right\} / \left(1 + \frac{R}{2R_b}\right)$, bridge balance factor,

R_b = impedance of bridge balance network, $\sim 11K \Omega$,

μ = Poisson's ratio = 0.33.

Taking the ratio of Equation (1) to Equation (2), substituting values and re-arranging

$$\epsilon = \frac{130.47V_0}{(R_C + 175)V_C - 203.56V_0}$$

or, since V_0 and V_C are proportional to the recorded digital signals, D_0 and D_C , and allowing for signal offset, D_0' , we have

$$\epsilon = \frac{130.47(D_0 - D_0')}{(R_C + 175)D_C - 203.56(D_0 - D_0')}$$

AFTRAS was carried in the gun bay, so that the lead length was somewhat different to that used for AFDAS. However, this difference is estimated to affect the value of K by less than 0.1%, and it has been ignored. AFTRAS could be switched on and off from the cockpit, independently of AFDAS. An event marker could also be operated from the cockpit. Instrumentation incompatibilities precluded the simultaneous feeding of AFDAS and AFTRAS from a single gauge bridge and so companion gauges 21T on the opposite side of the fin post to 21C (Fig. 1) and 1.4T on the opposite wing to 18T (Fig. 2) were connected to AFTRAS.

2.3 Strain Gauges

All strains were measured by four active arm (two tension, two Poisson) e.r.s.g. bridges formed from $350 \Omega \pm 0.3\%$. Micromeasurements type WK-13-K250BG-350 gauges with gauge factor $2.09 \pm 0.5\%$. Poisson's ratio, μ , was assumed to be 0.33 so that the bridge factor, $2(1 + \mu)$, = 2.66.

The disposition of the gauge bridges allows separate excitation of the two pairs, pitching excites 1.4T and 18T, but not 21T or C whereas yawing or rolling excites the fin gauges without substantial stressing of the wings.

2.4 Calibration

Earlier data (flight 12, dated 22/9/78) were analysed to provide a means of estimating the AFDAS gauge output from the AFTRAS measured strain. For symmetric manoeuvres the regression of 18T upon 1.4T was linear and, omitting offset,

$$\epsilon_{18T} = 1.031\epsilon_{1.4T}.$$

The presence of roll during a manoeuvre caused considerable deviation (Fig. 4) because, being on opposite wings, gauges 1.4T and 18T were oppositely excited during roll accelerations.

The regression of 21C upon 21T was non-linear (Fig. 5). A quadratic approximation yielded, omitting offset,

$$\epsilon_{21C} = -1.0273\epsilon_{21T} - 0.000192\epsilon_{21T}^2.$$

The residual S.D. about this regression, estimated from the residual sum of squares, is $6.5\mu\epsilon$, and the variance of the regression coefficients is negligible.

Variations in gauge output may have arisen in the year since the calibration flight, but experimental constraints have forced these to be ignored. During the analysis it was assumed that zero strain existed for the fin gauges in on-ground measurements, and for wing gauges at $N_z = 0$. Although this necessary assumption cannot be justified by theory or experiment it is in reasonable accord with experience.

3. TRIALS AND ANALYSIS

3.1 Flight Profiles

Although dedicated flights were requested, only three short segments, in flights 30, 44 and 50 (Table 3), were available for analysis. These were obtained by switching on AFDAS and eventing AFTRAS, nearly simultaneously, in level flights, performing a nominated set of manoeuvres to excite wings (flight 30) or fin (flights 44 and 50) (Fig. 6) and switching off/eventing as for the start of the record.

The AFDAS segment of flight 30 consisted of a series of pitching manoeuvres, substantially roll-free at peak load, to the load sequence $N_z = +1, -2.1, +5.7, -1.9, +5.9, -1.7, +1.5, +6.3, +1g$, as measured by the cockpit 'g' meter. This sequence was designed to ensure that at least one, and possibly two, transition strains were defined by producing counts in three adjacent cells at each end of the range. Fin gauge 21T was not recorded on AFTRAS. Values for altitude and airspeed for this segment were variable, average values were 400 kt, 14,000 ft.

The AFDAS segments for flights 44 and 50 consisted of rolls to left and right alternately, at about 200°/sec, repeated three times, each roll being separated by a short segment of level flight. Flight was at 400 kt IAS and 6000 ft altitude. Output from gauge 1.4T was recorded on AFTRAS, but all strain peaks were recorded at high roll rate.

Aircraft configuration varied between flights, resulting in differences in mass and mass distribution. These differences, detailed in Table 3, were unlikely to have affected fin strains, but may have influenced wing strains.

3.2 Data Analysis—Range-Mean-Pair Count

The turning points from AFTRAS records were transformed to engineering units and corrected to probable AFDAS gauge reading as described. The corrected strains (Table 4) were subjected to a range-mean-pair count, assuming the transition strains recalculated at ARL. The method of counting is illustrated in Figure 7.

In this figure the "pre-flight stack" represents the unpaired turning points obtained from the IDRU output from the preceding flight. Where range-pair counts arise from pairing these turning points they necessarily conform to the AFDAS count; and so are no help in the comparison with AFTRAS. The "turning points from flight record" are those turning points giving rise to useful range-pairs, and the "end stack" represents the unpaired turning points from the flights. The end stack and any unpaired turning points from the pre-flight stack will compare with end stack contents in the IDRU readout. The logic ensures that a turning point is always stored in stack level 0. A range-pair is counted when two adjacent turning points are preceded by one at a higher level and followed by one at a lower level or vice versa. The first five turning points in the sequence of Figure 7 are entries in the pre-flight stack and have not yet been consummated into range-pairs. The first turning point in the flight record consummates range-pair No. 1 (by returning to level 11, of which an event is stored in the stack), and the next two turning points, together with the excursion into level 5 and beyond, consummates range-pair No. 2. Return to level 0 consummates range-pairs 3 and 4 from the pre-flight stack.

The same number of range-mean-pairs were obtained by this process as were counted by AFDAS, but counts were sometimes assigned to adjacent cells in the count half-matrix (Fig. 8a-e).

3.3 Data Analysis—Estimate of Gain

The possibility that the experimentally determined strain transition values derived by AFTRAS differed from values calculated from circuit parameters was further investigated by listing AFDAS count levels against AFTRAS strains (Table 5). Pairs of values were then plotted and lines were drawn through the data to represent the overall gains for AFDAS.

For gauge 21C the gain was fixed within narrow limits (Fig. 9) and is close to the value calculated at ARL. The probable transition strains are listed in column 3, Table 1. Figure 10 shows the result of using these strain transition values to count range-mean-pairs for gauge 21C.

The position for gauge 18T is less fortunate. Due to a misunderstanding the AFDAS zero was improperly set so that all the strain troughs occurred in level 0. In consequence the only information from this source was that the threshold strain, $1\epsilon_0$, was less negative than the smallest trough. Since all the peaks were in levels 11 and 12 no clear indication of slope was given. Although turning points at levels between 1 and 11 were present in flights 44 and 50, these were always accompanied by roll which, as has been stated, complicates the regression of 18T on 14T. Many of the data points were associated with overload on the roll channel. Since exact magnitudes were not available a more complex model would not help even if it could be constructed.

All of the data for gauge 18T has been plotted in Figure 11 which illustrates the difficulties in deriving a gain for this channel.

A set of experimental transition strains has been derived (Table 2, column 3) from Figure 11, and it has been used to obtain range-pair counts for all three flight segments (Fig. 12). Many anomalies in the distribution of counts remain.

It is planned to produce continuous recording equipment which can sample from the same gauge as AFDAS, and to operate the two systems together over a large number of flights. Many of the limitations of these trials will thereby be overcome.

3.4 Data Analysis—Comparison of Memory Channels

The range-pair counter was switched on for portions of 18 flights in addition to the dedicated segments already analysed. Counts recorded in the several memory channels fed from a single gauge showed only trivial differences (Fig. 13a,b) which could be explained by postulating small differences in signal level at the time of sampling.

4. CONCLUSION

A prototype version of the Aircraft Fatigue Data Analysis System (AFDAS) has been evaluated in flight trials by comparison with continuously recorded data. Over a limited period of test the range-mean-pairs count of strain cycles was the same for both sets of data, and the gains calculated for the AFDAS equal those deduced from the continuous record.

Two interesting observations, which might repay closer analysis, were the effect of roll on wing strains, and the non-linear connection between strains on opposite sides of the finpost. Reference to Table 1, which compares calculated and experimental transition strains, indicates that some small uncertainty exists in the determination of offset, amounting to $20 \mu\epsilon$ and $78 \mu\epsilon$ for gauges 21C and 18T respectively.

REFERENCES

1. Goodrige, M. J., and Wood, L. E.—AFDAS - An Aircraft Fatigue Data Analysis System. Presented at the Conference of Aust. Institute of Engineers, Adelaide, April 1980.
2. Anderson, B. E., and Woodall, G.—Macchi MB326H Flight Trials (Stage 3). Instrumentation and Flight Profiles. ARL Structures Note 432, September 1976.
3. Fraser, R. C.—A One-pass Method for Counting Range-Mean-Pair Cycles for Fatigue Analysis. ARL Structures Note 454, June 1979.
4. Patterson, A. K.—ARL Note, in preparation.

TABLE 1

Transition Voltages and Strains at Fin and Wing Gauges

Transit from to	Volts (V_j)	Strain ($\mu\epsilon$) at gauge					
		21C			18T		
		(1)	(2)	(3)	(1)	(2)	(3)
0 1	-2.459	-999	-945	-925	-540	-508	-430
1 2	-2.107	-856	-809	-789	-340	-313	-234
2 3	-1.756	-713	-675	-653	-140	-119	-39
3 4	-1.403	-570	-539	-517	60	76	157
4 5	-1.056	-428	-406	-381	260	267	353
5 6	-0.684	-285	-263	-245	460	473	549
6 7	-0.332	-142	-128	-109	660	667	744
7 8	0.013	0.4	5	28	860	858	940
8 9	0.366	143	141	164	1060	1053	1135
9 10	0.718	286	276	300	1260	1248	1331
10 11	1.091	428	419	436	1460	1454	1527
11 12	1.438	571	552	572	1660	1645	1723
12 13	1.792	714	688	708	1860	1841	1918
13 14	2.145	857	824	844	2060	2036	2114
14 15	2.500	1000	960	980	2260	2232	2310

(1) Values provided by B.Ae.A.

(2) Values re-calculated at ARL.

(3) Probable threshold strains from flight trials.

TABLE 2

Calibration Data for AFTRAS

Flight No.	Channel	Gauge No.	Amp. No.	Cal R_c resist. ($K \Omega$)	Strain equivalent	$D_c/2$ cal step	D_0' strain (zero)
12 30 44 & 50	18	21C	30	38.860	NOT USED	1636.9	2032
	19	21T	25	38.884		1623.7	2038
	24	1.4T	46	38.838		1527.0	2265
	26	18T	48	38.760		1477.6	1856
	26	1.4T	29	38.871		821.5	1944
	26	1.4T	24	38.871		821.3	1944
	27	21T	30	38.860		820.4	1820

TABLE 3
Aircraft Configuration and Manoeuvres Performed in AFDAS Flight Segments

Flight No.	Aircraft configuration	Manoeuvres recorded
30 (flown 12/10/79)	Supersonic tanks; 2 × sidewinders and rails; all-up weight (AUW), 22,693 lbs at take off; Fuel at start, 798 gal; SG, 8.02 lb/gal. * Fuel at mid-point of AFDAS segment, 250 gals; AUW, 18,244 lbs; IAS variable around 400 Kt; altitude variable around 14,000 ft.	pitch up— pitch down −2.1g, +5.7g, −1.9g, +5.9g, −1.7g, +6.1g, −1.5g, +6.3g at cockpit
44 (flown 1/11/79)	2 × sidewinders and rails; matra and pylon; AUW, 20,991 lbs at TO; fuel at TO, 562 gals. * Fuel at mid-point of AFDAS segment, 190 gals; AUW, 18,200 lbs; IAS, 400 Kt; altitude, 6000 ft.	3 off left and right rolls at 200°/sec
50 (flown 9/11/79)	Supersonic tanks; 2 × sidewinders and rails; matra and pylon; AUW at TO, 23,019 lbs; fuel at TO, 775 gals. * Fuel at mid-point of AFDAS segment, 80 gals; AUW, 174W lbs; IAS, 400 Kt; Altitude, 6000 ft.	As 44
General	AFDAS switched on and off at 1g. AFTRAS evented at switching.	

* Fuel remaining probably underestimated; fuel flow sensor to be recalibrated.

TABLE 4A

Sequence of Strain Turning Points for Three Flight Segments
Measured on AFTRAS at gauge 1·4T and corrected to AFDAS strains at gauge 18T

Flight	30				44				50			
	1·4T		18T		1·4T		18T		1·4T		18T	
Gauge												
T.P. No.	Time*	C.U.†	Strain‡	Strain	Time	C.U.	Strain	Strain	Time	C.U.	Strain	Strain
1	2698	1564	-771·9	-795·8	1489	2320	765·8	789·5	2259	2156	431·2	444·6
2	2739	2695	1531·0	1578·5	1491	2141	401·0	413·4	2271	2362	850·8	877·2
3	2758	1659	-579·1	-597·1	1494	2509	1151·4	1187·1	2273	2105	327·5	337·6
4	2806	2726	1594·3	1643·8	1495	2084	284·9	293·8	2276	2559	1252·6	1291·5
5	2836	1679	-538·5	-555·2	1500	2418	965·7	995·6	2277	2106	329·5	339·7
6	2883	2731	1604·6	1654·3	1501	2150	419·3	432·3	2282	2502	1136·3	1171·6
7	2920	1716	-463·4	-477·7	1506	2605	1347·4	1389·2	2284	2002	117·9	121·6
8	2980	2765	1674·1	1726·0	1507	2032	179·1	184·6	2285	2311	746·9	770·1
9					1513	2464	1059·5	1092·4	2285	2159	437·4	450·9
10					1514	2101	319·5	329·4	2287	2586	1307·7	1348·3
11					1519	2592	1320·9	1361·9	2288	2148	415·0	427·8
12					1520	2052	219·8	226·6	2295	2486	1103·7	1137·9
13					1523	2232	586·4	604·6	2297	2016	146·4	150·9
14									2298	2286	696·0	717·6
15									2298	2123	364·1	385·4
16									2300	2578	1291·4	1331·5

* Time in half-seconds since take-off.

† Computer units of strain from arbitrary zero.

‡ Engineering strain, mean-strain units, assuming zero strain at zero load factor.

TABLE 4B
As Table 4A, but for AFTRAS gauge 21T and AFDAS gauge 21C

Flight Gauge T.P. No.	44				50			
	21T			21C Strain	21T			21C Strain
	Time	C.U.	Strain		Time	C.U.	Strain	
1	1487	1521	-608.5	554.0	2270	1452	-748.8	661.5
2	1489	1937	238.4	-255.8	2274	2478	1343.2	-1726.4
3	1490	1856	73.3	-76.4	2277	1499	-653.2	589.1
4	1493	2414	1212.3	-1527.7	2278	1940	244.5	-262.7
5	1495	1512	-626.8	568.4	2281	1031	-1603.2	1153.2
6	1496	1930	224.2	-239.9	2283	2165	703.6	-817.8
7	1499	1179	-1303.1	1012.5	2284	1928	220.1	-235.4
8	1501	2083	536.2	-606.1	2286	2541	1472.1	-1928.5
9	1502	1841	42.8	-44.3	2288	1372	-911.3	776.6
10	1505	2600	1592.8	-2123.7	2289	1970	305.7	-332.0
11	1506	1363	-929.6	789.0	2294	1120	-1422.8	1072.7
12	1507	1982	330.2	-360.1	2296	2201	777.1	-914.3
13	1512	1111	-1441.0	1081.4	2297	1932	228.2	-244.5
14	1514	2117	605.6	-692.5	2299	2489	1365.7	-1761.2
15	1515	1720	-203.6	201.2	2301	1415	-823.9	716.0
16	1518	2646	1687.0	-2279.8	2302	2012	391.4	-431.5
17	1520	1358	-939.7	795.7	2304	1764	-114.1	114.7
18	1521	1985	336.3	-367.2	2306	1873	108.0	-113.2
19					2307	1789	-63.1	64.1
20					2309	1891	144.7	-152.6
21					2310	1756	-130.3	130.6
22					2311	1872	105.9	-111.0
23					2312	1761	-120.2	120.7
24					2313	1895	152.8	-161.5

Corrected Measured Strain
With probable AFDAS level

[illegible]





FIG 1 FIN POST GAUGES 21T AND 21C



Scale 2/5

FIG 2 WING MAIN SPAR GAUGES 1.4T AND 18T




FIG 3 AFDAS INPUT SIGNAL CONFIGURATION




FIG 4 CORRELATION BETWEEN STRAINS MEASURED ON GAUGES 1.4T AND 18T, FLIGHT 12.




FIG 5 CORRECTION CURVE FOR ESTIMATING STRAIN AT
GAUGE 21C FROM MEASURED STRAIN AT 21T





FIG 6 TIME HISTORIES OF STRAIN

Flight 44, Channel 0 Gauge 21C
transition strains from Table 1 Col B.



(a) — Turning point sequence

1 2 3 4 5 6 7 8 9 10

Levels → (6,11), (6,7), (4,11), (0,12), (6,12), (3,7), (0,15), (5,13), (3,9), (0,15)

(b) — Range — mean — pairs, in order of counting.

* Pre flight stack depends on past flying,
not available from AFTRAS records, and
is taken from AFDAS.

FIG 7 METHOD OF COUNTING RANGE MEAN PAIRS FROM AFTRAS RECORD.

AFDAS output for Flight 30 Channel 1




FIG 8(a) COMPARISON OF RANGE-MEAN-PAIR COUNTS GAUGE 18T

FIG 8(b) AS 8(a) FOR GAUGE 18T

Stack *	43	44
	1	1
	1	1
	+	-
		$\frac{1}{1}$
	1	1
	1	1

Flight

* +, - = Termination level and sign



A=AFDAS
B=AFTRAS

Flight	Stack #	
	49	50
	1	1
	-	-
	1	1 0
		0 1
	1	1

* +, . = Termination level and sign



A=AFDAS
B=AFTRAS

FIG 8(c) AS 8(a) FOR GAUGE 18T

AFDAS output for Flight 44 Channel 0




FIG 8(d) AS 8(a) FOR GAUGE 21T

Flight

[illegible]

Termination level and sign



A=AFDAS
B=AFTRAS

FIG 8(e) AS 8(a) FOR GAUGE 21T




FIG 9 AFDAS LEVEL FOR GAUGE 21C vs CORRECTED STRAIN FROM AFTRAS RECORD FOR GAUGE 21T




FIG 10 COMPARISON OF RANGE—MEAN PAIR COUNTS




FIG 11 AFDAS LEVEL FOR GAUGE 18T vs CORRECTED STRAIN FROM AFTRAS RECORD FOR GAUGE 1.4T

AFDAS output for Flights 30, 44 & 50 Channel 1, Gauge 18T




FIG 12 COMPARISON OF RANGE-MEAN PAIR COUNTS

AFDAS output for all Flights Channels 0, 2




FIG 13(a) COMPARISON OF RANGE—MEAN PAIR COUNTS

AFDAS output for all Flights Channels 1, 3, 4




FIG 13(b) AS 13(a)

DISTRIBUTION

Copy No.

AUSTRALIA

Department of Defence

Central Office

Chief Defence Scientist	1
Deputy Chief Defence Scientist	2
Superintendent, Science and Technology Programs	3
Australian Defence Scientific and Technical Representative (UK)	—
Counsellor, Defence Science (USA)	—
Joint Intelligence Organisation	4
Defence Central Library	5
Document Exchange Centre, DISB	6-22
DGAD (NCO)	23

Aeronautical Research Laboratories

Chief Superintendent	24
Library	25
Superintendent—Structures Division	26
Divisional File—Structures	27
Author: P. J. Howard	28

Materials Research Laboratories

Library	29
---------	----

Defence Research Centre, Salisbury

Library	30
---------	----

Defence Industry and Material Policy

FAS	31
-----	----

Central Studies Establishment

Information Centre	32
--------------------	----

Engineering Development Establishment

Library	33
---------	----

RAN Research Laboratory

Library	34
---------	----

Defence Regional Office

Library	35
---------	----

DIDB [SA]

Att. Mr. C. Pugsley	36-37
---------------------	-------

Navy Office

Naval Scientific Adviser	38
--------------------------	----

Army Office

Army Scientific Adviser	39
US Army Standardisation Group	40

Air Force Office

Aircraft Research and Development Unit, Scientific Flight Group	41
Air Force Scientific Adviser	42
Technical Division Library	43
DGOR—AF	44
DGAIRENG	45
HQOC	46

Department of Productivity

Government Aircraft Factories	
Manager	47
Library	48

Department of Science and the Environment

Bureau of Meteorology, Publications Officer	49
---	----

Department of Transport

Secretary	50
Library	51
Airworthiness Group, Mr. K. O'Brien	52

Statutory, State Authorities and Industry

CSIRO, Mechanical Engineering Division, Chief	53
CSIRO, National Measurement Laboratory, Chief	54
CSIRO, Materials Science Division, Director	55
Qantas, Library	56
Trans-Australia Airlines, Library	57
Ansett Airlines of Australia, Library	58
BHP, Central Research Laboratories, New South Wales	59
BHP, Melbourne Research Laboratories	60
Commonwealth Aircraft Corporation, Library	61
Hawker de Havilland Pty. Ltd.	
Librarian, Bankstown	62
Manager, Lidcombe	63
British Aerospace Australia, Att. Mr. E. Chambers	64-65

Universities and Colleges

New South Wales	Assoc. Professor R. W. Traill-Nash	66
RMIT	Library	67
	Mr. H. Millicer	68
	Mr. Pugh	69

CANADA

CAARC Coordinator Structures	70
International Civil Aviation Organization, Library	71
NRC, National Aeronautical Establishment, Library	72
NRC, Division of Mechanical Engineering, Director	73

FRANCE

AGARD, Library	74
ONERA, Library	75
Service de Documentation, Technique de l'Aeronautique	76

INDIA

CAARC Co-ordinator	
Materials	77
Structures	78
Civil Aviation Department, Director	79
Defence Ministry, Aero Development Establishment, Library	80
Hindustan Aeronautics Ltd., Library	81
Indian Institute of Science, Library, Banqulore	82
Indian Institute of Technology, Library, Kanpur	83
National Aeronautical Laboratory, Director	84

INTERNATIONAL COMMITTEE ON AERONAUTICAL FATIGUE

Per Australian ICAF Representative	85-111
------------------------------------	--------

ISRAEL

Technion-Israel Institute of Technology, Professor J. Singer	112
--	-----

ITALY

Associazione Italiana di Aeronautica e Astronautica	113
---	-----

JAPAN

National Aerospace Laboratory, Library	114
Tokyo University, Inst. of Space and Aeroscience	115

NETHERLANDS

Central Org. for Applied Science Research TNO, Library	116
National Aerospace Laboratory (NLR), Library	117

NEW ZEALAND

Defence Scientific Establishment, Librarian	118
Transport Ministry, Civil Aviation Division, Library	119

SWEDEN

Aeronautical Research Institute	120
Kungliga Tekniska Hogskolan	121
SAAB-Scania, Library	122

SWITZERLAND

F & W Emmen	123
-------------	-----

UNITED KINGDOM

Aeronautical Research Council, Secretary	124
CAARC, Secretary	125
Royal Aircraft Establishment:	
Farnborough, Library	126
Bedford, Library	127
Military Vehicles Engineering Establishment	128
National Engineering Laboratories, Superintendent	129
National Physical Laboratories, Libraries	130
British Library	
Science Reference Library	131
Lending Division	132

Naval Construction Research Establishment, Superintendent	133
CAARC Co-ordinator, Structures	134
Aircraft Research Association, Library	135
Motor Industries Research Association, Director	136
Rolls-Royce (1971) Ltd.	
Aero Division, Leavesdon, Chief Librarian	137
Aero Division, Bristol, Library	138
British Aerospace Corporation	
Kingston-Brough, Library	139
Manchester, Library	140
Kingston-upon-Thames, Library	141
Hatfield—Loxtock Division	142
Hatfield—Chester Group	143
British Hovercraft Corporation Ltd., Library	144
Fairey Engineering Ltd., Hydraulic Division	145
Short Brothers Ltd.	146
Westland Helicopters Ltd.	147

UNITED STATES OF AMERICA

NASA Scientific and Technical Information Facility	148
American Institute of Aeronautics and Astronautics	149
Applied Mechanics Review	150
Boeing Co.	
Head Office, Mr. R. Watson	151
Industrial Production Division	152
Cessna Aircraft Co., Executive Engineer	153
General Electric, Aircraft Engine Group	154
Lockheed Missiles and Space Company	155
Lockheed California Company	156
Lockheed Georgia Company	157
McDonnell Douglas Corporation, Director	158
Texas Instrument Co., Director	159
United Technologies Corporation, Pratt and Whitney Aircraft Group	160
Battelle Memorial Institute, Library	161

Spares	162-171
--------	---------

MED
8